

300M KVM EXTENDER MANUAL

Industrial Products

Information Release Screen Splicing

Video Conference Teaching Projection

We reserve the copyright have product details, if the parameters and a minor change and appearance from time to tome, the factory specifications shall prevail, the company reserves final interpretation

@ 2013. all rights reserved

Product Introduction

KVM Extender is one of our independent development products. The newest promoted KVM Extender has high quality of image, remote keyboard and mouse action does not have the time delay. It may widely apply in the computer, monitor, security, multimedia teaching systems and so on. It could extend keyboard, mouse and video ports on computer up to 300m. It promotes the function of anti-thunder and anti-jamming to make sure the security and stability.

Features

1. It can extend the power switch of the computer, keyboard, mouse and video port max of 300m
2. It can be switched from remote monitor to local monitor or switched from local monitor to remote monitor by the keystroke on the Sender or SCROLL on the local keyboard
3. Use the single cable (CAT5, CAT5E, CAT6), the cost is inexpensive
4. It supports (USB and PS/2 port) keyboard and mouse, it supports (VGA) port monitor
5. It can remove and insert the local and remote keyboard and mouse
6. Power on computer use the emulational keyboard and mouse
7. It supports DOS, Windows, Linux, Unix system
8. It does not need a driver, it is simple to install
9. The remote keyboard and mouse display is in real-time

10.The anti-jamming is strong

11.The anti-lightning and anti-invasion is strong Cascade operation for increasing the distance

12.Index of anti-lightning and anti-invasion: withstand air-discharge 15KV, contiguity-discharge 8KV

Parameter

input connector:	1-ch VGA+ 1-ch usb		
output connector:	VGA, 2-PS2		
local output:	HD15PIN (VGA)		
Distance and resolution	100M	200M	300M
	1920x1200	1600x1200	1400x900
bandwidth:	680MHZ		
input level range:	0.5-2.0Vp-p		
input level error:	less than 3mV		
input impedance:	75Ω		
output impedance:	75Ω		
echo ullage:	-30dB@5MHz		
Max DC compensation:	±5mV-0		
SNR:	60dB		
Connector standard:	HDB15, USB,Mini-DIN6,RJ45,ps2		

Video standard:	VGA, SVGA, XGA, SXGA, UXGA, LCD
Cable standard:	CAT5, CAT5E, CAT6 UTP
Power adapter:	DC12V/1A
operational temperature:	-25°C~+70°C
deposited temperature:	-40°C~+80°C
relative humidity:	0~95% (non-condensing)
MTBF:	>30000 hours

Packing List

1. KVM extender transmitter receiver
2. 12V/1A power adapter
3. USB cable
4. the manual
5. factory maintenance card

Application



